

Technical Specifications Contour S 1.4

Sensitivity (2.83 V/1 m):	85 dB
IEC Long Term Power Handling:	< 160 watts
Impedance, Nominal:	4 ohms
Frequency Response: (+/- 3 dB)	41 Hz – 25 kHz
Internal Cabinet Volume:	13 litres
Bass Principle:	Bass reflex
Weight:	12.6 kg
Dimensions (W x H x D):	188 x 404 x 360 mm
Crossover:	2 way
Crossover Frequencies:	1900 Hz
Crossover Slope:	Woofer 6 dB/octave; Tweeter 6 dB/octave
Recommended Placing:	Dynaudio Stand ⁴

Remarks:	Tweeter:	<ul style="list-style-type: none">• 28 mm soft dome – technology from Esotar²• Magnetic fluid• 5 mm machined aluminium front, with high heat-dissipation, integrated in baffle• Pure aluminium wire voice coil
	Woofer:	<ul style="list-style-type: none">• Die-cast chassis• 17 cm one-piece moulded MSP cone• 75 mm long throw pure aluminium wire voice coil, wound on Kapton[®] former• Neodymium magnet ring
	Crossover:	<ul style="list-style-type: none">• Thick glass fibre reinforced PCB with extra copper thickness• Capacitors with low loss dielectricum• Zero compression resistors• Inductors wounded on “air cores”• The crossover is impedance corrected