



Dynaudio Sub 6

Firmware update instructions

Skanderborg – February 28th, 2023

DYNAUDIO

Dynaudio A/S
Sverigesvej 15
DK-8660 Skanderborg
T: +45 8652 3411
dynaudio.com

Requirements

- Empty USB stick, formatted to FAT32. Max size is 8 GB.
- The latest firmware file downloaded from Sub 6 section on www.dynaudio.com

Firmware versions

There are two versions of the Sub 6 firmware.

The “**Standard**” firmware (05.0002) includes crossover presets to match following Dynaudio products:

- Confidence 20 / 30 / 50 / 60
- Contour 20i / 30i / 60i
- Evoke 10 / 20 / 30 / 50
- Heritage Special
- Special Forty

The “**Legacy**” firmware (105.0002) includes crossover presets to match following Dynaudio products:

- Confidence C1 / C2 / C4
- Contour 1.4 LE / 3.4 LE
- Contour 20 / 30 / 60
- Evidence Temptation / Platinum / Master
- Focus 20 XD / 30 XD / 60 XD
- Special Twenty-Five

Steps

1. Unzip the downloaded Zip file.
2. Copy the ‘*DYNAUDIO.bin*’ firmware file into the root directory of the USB stick.
3. Switch OFF the subwoofer with the rear-panel switch.
4. Insert the USB stick into the USB port at the rear panel labeled ‘Service’.
5. Switch ON the subwoofer with the rear-panel switch.
6. Your subwoofer will automatically download the firmware from the USB stick.
7. After this, let the sub install the full update, which should take 1-3 minutes.
DON'T TURN IT OFF.
8. During this update the LED will change from red to blue, and display various messages about the update progress.
9. After installation is complete, the LED will turn green and the display will return the message: *Update result: Success!*
10. Your firmware update procedure is now finished. Switch OFF the subwoofer, and remove the USB stick.
11. Switch ON the subwoofer.
12. Check the firmware version in the menu info screen.