

## Technical Specification | Audience 122

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power: Small size rooms:	>25 watts
Medium size rooms:	>65 watts
Large size rooms:	>125 watts
IEC Long Term Power Handling:	200 watts
Impedance, Nominal:	6 ohms
Impedance, (20-200 Hz):	3.9 - 11 ohms
Impedance, (200-20 kHz):	3.8 - 9.4 ohms
Impedance, Phase Shift (20-200 Hz):	-33° - +24°
Impedance, Phase Shift (200-20 kHz):	-8° - +28°
Impedance, HF (200 kHz):	11 ohms
Frequency Response (+/- 3 dB):	41 Hz - 22 kHz
Resonance Frequency:	45 Hz
Internal Cabinet Volume:	17 litres
Bass Principle:	Bass reflex
Weight:	14.5 kg
Dimensions (W x H x L):	165 x 969 x 256 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	2000 Hz
Crossover Slope:	Woofers 6 dB/oct; Tweeter 12 dB/oct
Connection:	CE compliant insulated gold binding posts
Recommended Placing:	Floor

Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. Pure aluminium wire voice coil. Rear chamber.
	Woofers: 2 x 15 cm polypropylene cone. 75 mm pure aluminium wire voice coil.
	Cabinet: Front baffle 28 mm MDF. Port plugs and spikes included. Bitumen damped enclosure.

### DYNAUDIO International GmbH

Ohepark 2  
21224 Rosengarten  
Germany  
Phone +49 (0)4108 - 4180 - 0  
Fax +49 (0)4108 - 4180 - 10  
E-Mail [info@dynaudio.de](mailto:info@dynaudio.de)