

Technical Specification | Audience 15

Sensitivity (2.83 V/1 m):	87 dB
Recommended Amp. Power:	Small size rooms: >20 watts Medium size rooms: >50 watts Large size rooms: -- watts
IEC Long Term Power Handling:	>150 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	3.6 - 14.4 ohms
Impedance, (200 - 20 kHz):	3.7 - 6.6 ohms
Impedance, Phase Shift (20 - 200 Hz):	-43.6° - +31.9°
Impedance, Phase Shift (200 - 20 kHz):	-12.1- +13.4°
Impedance, HF (200 kHz):	6.6 ohms
Frequency Response (+/- 3 dB):	40 Hz - 23 kHz
Resonance Frequency:	35 Hz
Internal Cabinet Volume:	20 litres
Bass Principle:	Bass reflex
Weight:	16 kg
Dimensions (W x H x L):	230 x 832 x 297 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	2600 Hz
Crossover Slope:	Woofer: 6 dB/oct, Tweeter 12 dB/oct
Connection:	OCOS + Gold binding posts
Recommended Placing:	Floor, free standing
Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die-cast aluminium front. Pure aluminium wire voice coil. Rear chamber. Woofer: 19 cm polypropylene cone. powerful magnet system. Spikes included.

DYNAUDIO International GmbH

Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0
Fax +49 (0)4108 - 4180 - 10
E-Mail info@dynaudio.de