DYNAUDIO
AUTHENTIC FIDELITY

Technical Specification_Audience 42 C

Sensitivity (2.83 V/1 m):		85 dB
Recommended Amp. Power:	Small size rooms:	>30 watts
	Medium size rooms:	>80 watts
	Large size rooms:	-- watts
IEC Long Term Power Handling:		150 watts
Impedance, Nominal:		4 ohms
Impedance, (20-200 Hz):		3.7 - 9.6 ohms
Impedance, (200-20 kHz):		3.7 - 19 ohms
Impedance, Phase Shift (20-200 Hz):		-27° - +26°
Impedance, Phase Shift (200-20 kHz):		-16° - +46°
Impedance, HF (200 kHz):		15 ohms
Frequency Response (+/- 3 dB):		55 Hz - 27 kHz
Resonance Frequency:		56 Hz
Internal Cabinet Volume:		6.1 litres
Bass Principle:		Bass reflex
Weight:		5.5 kg
Dimensions (W x H x L):		370 x 165 x 200 mm
Crossover:		2 way. The crossover is impedance corrected
Crossover Frequencies:		1800 Hz
Crossover Slope:		Woofer 6 dB/oct; Tweeter 6 dB/oct
Connection:		CE compliant insulated gold binding posts
Recommended Placing:		Above/below TV-set, or on a stand

Remarks:

Tweeter: 28 mm soft dome.
Magnetic fluid.
Pure aluminium wire voice coil.
Rear chamber.

Woofer: 15 cm polypropylene cone.
75 mm pure aluminium wire voice coil.

Cabinet: Front baffle 22 mm MDF.
Port plugs included.
Macnetic shielded.

Technical Specification_Audience 42 C

DYNAUDIO Vertriebs GmbH
Ohepark 2
21224 Rosengarten-Nenndorf
Telefon 04108 - 4180 - 0
Telefax 04108 - 4180 - 10
E-Mail d@dynaudio.de

ID. Nr. DE 118 543 967
HR Tostedt B 4757 • GF: W. Ehrenholz