

## Technical Specification | Audience 5

Sensitivity (2.83 V/1 m):	87 dB
Recommended Amp. Power:	Small size rooms: >20 watts Medium size rooms: >50 watts Large size rooms: -- watts
IEC Long Term Power Handling:	>150 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	4.1 - 11.3 ohms
Impedance, (200 - 20 kHz):	3.9 - 7.2 ohms
Impedance, Phase Shift (20 - 200 Hz):	-32.5° - +29.4°
Impedance, Phase Shift (200 - 20 kHz):	-16.4° - +20.0°
Impedance, HF (200 kHz):	12.8 ohms
Frequency Response (+/- 3 dB):	50 Hz - 20 kHz
Resonance Frequency:	43 Hz
Internal Cabinet Volume:	10.3 litres
Bass Principle:	Bass reflex
Weight:	5.5 kg
Dimensions (W x H x L):	205 x 310 x 240 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	5000 Hz
Crossover Slope:	Woofer: 6 dB/oct, Tweeter 12 dB/oct
Connection:	Gold binding posts
Recommended Placing:	Stand Wall - with port plugs Book shelf - with port plugs
Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. Protection grill. Pure aluminium wire voice coil.  Woofer: 17 cm with 75 mm pure aluminium wire voice coil.  The crossover include tweeter protection. Bitumen damped enclosure. Port plugs included. Also suitable for AV.

### DYNAUDIO International GmbH

Ohepark 2  
21224 Rosengarten  
Germany  
Phone +49 (0)4108 - 4180 - 0  
Fax +49 (0)4108 - 4180 - 10  
E-Mail [info@dynaudio.de](mailto:info@dynaudio.de)