

Technical Specification | Audience 50

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power:	Small size rooms: >25 watts Medium size rooms: >65 watts Large size rooms: -- watts
IEC Long Term Power Handling:	150 watts
Impedance, Nominal:	4 ohms
Impedance, (20 - 200 Hz):	3.6 - 11.5 ohms
Impedance, (200 - 20 kHz):	3.6 - 9.7 ohms
Impedance, Phase Shift (20 - 200 Hz):	-32.4° - +31.2°
Impedance, Phase Shift (200 - 20 kHz):	-9.6° - +29.7°
Impedance, HF (200 kHz):	7.1 ohms
Frequency Response (+/- 3 dB):	46 Hz - 27 kHz
Resonance Frequency:	47 Hz
Internal Cabinet Volume:	9.8 litres
Bass Principle:	Bass reflex
Weight:	6.9 kg
Dimensions (W x H x L):	204 x 330 x 256 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	2660 Hz
Crossover Slope:	Woofer: 6 dB/oct; Tweeter 12 dB/oct
Connection:	CE compliant insulated gold binding posts
Recommended Placing:	Stand
Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die-cast aluminium front. Pure aluminium wire voice coil. Rear chamber. Woofer: 17 cm polypropylene cone. 75 mm pure aluminium wire voice coil. Cabinet: Front baffle 19 mm MDF. Port plugs included.

DYNAUDIO International GmbH

Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0
Fax +49 (0)4108 - 4180 - 10
E-Mail info@dynaudio.de