

Technical Specification Audience 62

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power: Small size rooms:	>25 watts
Medium size rooms:	>65 watts
Large size rooms:	-- watts
IEC Long Term Power Handling:	150 watts
Impedance, Nominal:	4 ohms
Impedance, (20-200 Hz):	3.6 - 11 ohms
Impedance, (200-20 kHz):	3.6 - 9.6 ohms
Impedance, Phase Shift (20-200 Hz):	-35° - +33°
Impedance, Phase Shift (200-20 kHz):	-10° - +30°
Impedance, HF (200 kHz):	5.9 ohms
Frequency Response (+/- 3 dB):	38 Hz - 25 kHz
Resonance Frequency:	45 Hz
Internal Cabinet Volume:	12 litres
Bass Principle:	Bass reflex
Weight:	13.6 kg
Dimensions (W x H x L):	204 x 859 x 256 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	2800 Hz
Crossover Slope:	Woofer 6 dB/oct; Tweeter 12 dB/oct
Connection:	CE compliant insulated gold binding posts
Recommended Placing:	Floor

Remarks:

- Tweeter: 28 mm soft dome.
Magnetic fluid.
Pure aluminium wire voice coil.
Rear chamber.
- Woofer: 17 cm polypropylene cone.
75 mm pure aluminium wire voice coil.
- Cabinet: Front baffle 28 mm MDF.
Port plugs and spikes included.
Bitumen damped enclosure.

DYNAUDIO Vertriebs GmbH
Ohepark 2
21224 Rosengarten-Nenndorf
Telefon 04108 - 4180 - 0
Telefax 04108 - 4180 - 10
E-Mail d@dynaudio.de