

Technical Specification | Audience LR120+

Sensitivity (2.83 V/1 m):	86 dB
Recommended Amp. Power:	Small size rooms: >25 watts Medium size rooms: >65 watts Large size rooms: >125 watts
IEC Long Term Power Handling:	200 watts
Impedance, Nominal:	6 ohms
Impedance, (20 - 200 Hz):	4.2 - 11.6 ohms
Impedance, (200 - 20 kHz):	4.2 - 13.1 ohms
Impedance, Phase Shift (20 - 200 Hz):	-30.0° - +27.1°
Impedance, Phase Shift (200 - 20 kHz):	-24.8- +30.8°
Impedance, HF (200 kHz):	6.7 ohms
Frequency Response (+/- 3 dB):	37 Hz - 22 kHz
Resonance Frequency:	47 Hz
Internal Cabinet Volume:	17 litres
Bass Principle:	Bass reflex
Weight:	11.4 kg
Dimensions (W x H x L):	165 x 570 x 320 mm
Crossover:	2 way. The crossover is impedance corrected
Crossover Frequencies:	2510 Hz
Crossover Slope:	Woofers: 6 dB/oct; Tweeter 12 dB/oct
Connection:	CE compliant insulated gold binding posts
Recommended Placing:	On a stand or underneath TV-Set
Remarks:	Tweeter: 28 mm soft dome. Magnetic fluid. 4 mm die-cast aluminium front. Pure aluminium wire voice coil. Rear chamber. Woofers: 2 x 15 cm polypropylene cone. 75 mm pure aluminium wire voice coil. Cabinet: Front baffle 22 mm MDF. Port plugs included.

DYNAUDIO International GmbH

Ohepark 2
21224 Rosengarten
Germany
Phone +49 (0)4108 - 4180 - 0
Fax +49 (0)4108 - 4180 - 10
E-Mail info@dynaudio.de